



Build Volume: 500×500×700 mm

Printing Temperature : Up to 500°C

Hot Bed Temperature: : Up to 180°C

Chamber Temperature : Up to 150°C

Filament Box Temperature: Up to 65°C

Extrusion System : Individual Lifting Liquid Cooling Dual Extruder

Majority of the Materials on Market : PEEK, CF-PEEK, PEKK, CF-PEKK, PEI

1010/9085, PPSU, PC, CF-PC, PA, CF-PA, GF-PA, ASA, ABS, CF-ABS, PETG

HIPS, TPU, PLA, CF-PLA, PVA...

MAGIC-HT-MAX

Specification

Principle: Fused Filament Fabrication (FFF)	File Type: STL, OBJ, 3MF, GCODE
Filament Diameter: 1.75 mm	Data Transmission: SD Card, WIFI, USB
Layer Thickness: 0.05 – 0.3 mm	Machine Size: 1080×1380×1950 mm
Position Resolution: X/Y: 8.65 μm Z: 2.75 μm	Net Weight: 750KG
Supplied Software: IEMAI 3D EXPERT	Gross Weight: 850KG
Other Software: Cura, Simplify3D	Power: 200~250 V, 50~60 Hz 6500W

Features

Power Failure Recovery	Auto Leveling
Filament Absent Warning	Vacuum Adsorption Platform
Auto-Shut Down System	Extruder Auto-Cleaning
Camera Monitoring	Dual Extruder Modularization

MAGIC-HT-MAX is specially designed for engineering plastic, with a temperature of 500°C extruder temperature and 180°C hot bed temperature and 150°C chamber temperature, it is able to support most of the plastic on the market. It had a modular mechanism on the extruder which allow it to have simple maintenance and support the corporate print with water soluble material.